



**Sales Outline Drawing**Revision **A****Specifications:**

Oscillation Frequency (Hz)	2048
Operating Voltage (Vdc)	1.25 ~ 2.5
Rated Voltage (Vdc)	1.5
Current Consumption Max. (mA)	40 at Rated Voltage
Sound Pressure Level (dB/min)	85 at 10cm at Rated Voltage
Coil Resistance ( $\Omega$ )	$16 \pm 2$
Operating Temperature ( $^{\circ}\text{C}$ )	$-20 \sim +70$
Storage Temperature ( $^{\circ}\text{C}$ )	$-30 \sim +80$
Lead Pin	Tin Plated Brass
Housing	ABS 757 UL94HB plastic resin (Color: Black)
Weight (Grams)	1.4
Condition by wave soldering ( $^{\circ}\text{C}$ )	$245 \pm 5 / 3 \pm 0.5$ sec
Condition by hand soldering ( $^{\circ}\text{C}$ )	$350 \pm 20 /$ within 5 sec
Options	For other options contact factory

PS:  $V_{p-p} = 1/2$ duty, square wave**RoHS Compliant****Dimensions:** (units: mm)**Recommended Driving Circuit:**

The base current  $I_b$  should be high enough so that it saturates the collector current of the transistor with the CB load.